


Dinesen Floors a/s T +45 7455 2140  
 Klovtoftvej 2, Jels F +45 7455 2976  
 6630 Rødding, Denmark E info@dinesen.com

dinesen.com cvr/vat 33920717

Concerning

Declaration of Performance No.: Layers Ash Dop 2013-3			
1. Unique identification code for the product type		Dinesen – Lamella-constructed – Ash	
2. Type, batch or serial number etc.		Products described as Dinesen Ash (Fraxinus Excelsior) with a minimum thickness of 19 mm and a minimum density of 650 kg/m <sup>3</sup>	
3. Intended use of the construction product		Floors for interior use	
4. Manufacturer's name		Dinesen Floors a/s Klovtoftvej 2, Jels 6630 Rødding, Denmark	
5. Name and address of the authorized representative		Not applicable	
6. Assessment and verification of performance constancy		AVCP 4	
7. Task of notified institution(s)		Not applicable	
8. Declared performance			
Properties (table ZA.1):	Declared performance:	Reference:	
Reaction to fire	D <sub>fl,s1</sub>	Table 1	EN 14342:2013
Formaldehyde emission	E1	Annex A	
Pentachlorophenol	≤ 5 ppm	Table ZA.1	
Breaking strength	NPD (no performance determined)	EN 1533	
Slipperiness	NPD (no performance determined)	CEN/TS 15676	
Thermal conductivity	0,17 W/mK	Table 2	
Biological durability	Usage class 1	EN 335	
Performance for the construction product stated in points 1 and 2 conforms to the declared performance in point 8.			
This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 4.			
Jels, 05.10.2023			
Place and date		Jeppe Fabricius Olsen, Head of Technical, Commercial	